



FEATURES

- Powerful, stable tour sound amplifiers
- Superior sound quality
- Low THD and High dumping factor for excellent sound quality
- Higher operational reliability
- 4 High speed stepless fans
- Suitable for tour sound and project installations



MODEL NO	CLA 7800	CLA 9000
8Ω stereo power	2x2800w	2x3200w
4Ω stereo power	2x3900w	2x4500w
8Ω Bridge Mono power	5200W	6000W
4Ω Bridge Mono power	8800W	10000W
Frequency Response	20HZ-20KHZ±0.5dB	20HZ-20KHZ±0.5dB
THD+N(20Hz-20KHz)%	<0.08%	<0.08%
Signal noise rate (dB)	>110dB	>110dB
Damping Factor (8Ω, 20Hz-1KHz)	1000	1000
Input connectors (per ch.)	3-pin XLR, electronically balanced	3-pin XLR, electronically balanced
Link connectors(per ch.)	XLR, 3 pin male	XLR, 3 pin male
Protection	Protection of short circuit, open circuit, overheat, overload, DC etc.	Protection of short circuit, open circuit, overheat, overload, DC etc.
Output topology	4u Class H	4u Class H
Output connectors	Speakon Connectors (NEUTRIK)	Speakon Connectors (NEUTRIK)
Input Impedance	20KΩ Balanced, 10KΩ Unbalanced	20KΩ Balanced, 10KΩ Unbalanced
Power requirement	200-240V-50-60Hz	200-240V-50-60Hz